



DecorLux® HT2.0 Heterogeneous

Material Data Sheet

Color Line



RL-5501



RL-5505



RL-5504




RL-5502



RL-5507




RL-5511



RL-5510



RL-5512



RL-601



RL-613



RL-603



RL-610




RL-612



RL-602



RL-609



RL-604



RL-606



RL-605



RL-607



RL-611



DecorLux® HT2.0 Heterogeneous

Material Data Sheet

DESCRIPTION

Total thickness	EN 428	mm	2.0
Wear layer thickness	En 429	mm	0.4
Weight	EN 430	g/m ²	2300/2500
Width of sheet	EN 426	cm	200
Length of sheet	EN 426	lm	20

CLASSIFICATION

Fire rating	DIN 4102	-	B1
	GB8624-2006	-	GB 8624 B _{fl-s1}
Toxic testing	GB 18586-2001	-	-
Static electrical propensity	EN 1815	KV	<2
Slip resistance dry	EN 13893	-	≥0.3
Slip resistance dry	DIN 51 130	class	R9

PERFORMANCE

Abrasion group	EN 649	Group	P
Dimensional stability	EN 434	%	≤0.4
Residual indentation	EN 433	mm	0.04
Flexibility	EN 435	-	Excellent
Colour fastness	EN20 105 - B02	Degree	≥6
Chemical products resistance	EN 423	-	OK
Surface treatment	-	-	UV
Impact sound reduction	EN ISO 717/2	-	Approx. + 4 dB
Indentation	EN433	mm	Approx. 0.04
Hygiene treatment	MRSA	-	Very good
Castor wheel test	EN425	-	Suitable