



DecorLux® HT3.0 Heterogeneous

Material Data Sheet

Color Line




RL-801




RL-804




RL-802




RL-809



RL-808



RL-807




RL-806




RL-805



RL-810




RL-812



RL-103



RL-105



RL-101



RL-104




RL-107



RL-109




RL-106



RL-108



RL-111



RL-113



DecorLux® HT3.0 Heterogeneous

Material Data Sheet

DESCRIPTION

Total thickness	EN 428	mm	3.0
Wear layer thickness	En 429	mm	0.5
Weight	EN 430	g/m ²	2800/3200
Width of sheet	EN 426	cm	200
Length of sheet	EN 426	lm	15

CLASSIFICATION

Fire rating	DIN 4102	-	B1
	GB8624-2006	-	GB 8624 B _{fl-s1}
Toxic testing	GB 18586-2001	-	
Static electrical propensity	EN 1815	KV	<2
Slip resistance dry	EN 13893	-	≥0.3
Slip resistance dry	DIN 51 130	class	R9

PERFORMANCE

Abrasion group	EN 649	Group	P
Dimensional stability	EN 434	%	≤0.4
Residual indentation	EN 433	mm	0.04
Flexibility	EN 435	-	Excellent
Colour fastness	EN20 105 - B02	Degree	≥6
Chemical products resistance	EN 423	-	OK
Surface treatment	-	-	UV
Impact sound reduction	EN ISO 717/2	-	Approx. + 4 dB
Indentation	EN433	mm	Approx. 0.04
Hygiene treatment	MRSA	-	Very good
Castor wheel test	EN425	-	Suitable