DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011



No. FB750 - 20170703

1. Unique identification code of the product-type: FB750

Intended use/es: A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

3. Manufacturer: Tremco Illbruck Limited, Coupland Road, Hindley Green, Wigan. WN24HT

5. System/s of AVCP: System 1

6. European Assessment Document: ETAG 026 edition 2011 part 2

European Technical Assessment: ETA 17/0392

Technical Assessment Body: CPR Notified Body UL International UK Ltd, No. 0843

Notified body/ies: CPR Notified Body UL International UK Ltd, No. 0843

7. Declared performance/s

Basic Work Requirement	Performance	
Mechanical resistance and stability		
None	Not relevant	
Safety in case of fire		
Reaction to fire (EN 13501-1)	Class E	
Resistance to fire (EN 13501-2)	See ETA17/0392 Annex A	
Hygiene, Health and the Environment		
Air Permeability (EN 1026:2000)	See ETA17/0392 Annex B	
Water Permeability (ETAG 026-2 Annex C)	NPD	
Release of dangerous substances	Declaration of manufacturer – Uses categories IA3, S/W3	
Safety in Use		
Mechanical Resistance and stability (EOTA TR001:2003)	NPD	
Resistance to Impact / movement (EOTA TR001:2003)	NPD	
Adhesion (EOTA TR001:2003)	NPD	
Protection against noise		
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	See ETA17/0392 Annex C	
Energy, Economy and Heat Retention		
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD	
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD	
General Aspects Relating to fitness for use		
Durability and Serviceability (EOTA TR 024:2009)	Z ₁	

NPD = No Performance Determined

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Leader Sealants and Coatings

At Wigan on 9 October 2017

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.



2.

CE

Tremco Illbruck Limited
Coupland Road, Hindley Green, Wigan, WN2 4HT
17
0843-CPR-0369

0843-CPR-0369 FB750 – 20170703 www.nullifire.com/FB750

> EN 1366 Part 3 ETA 17/0392 ETAG 26, Part 2

A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

Essential Characteristic	Performance	
Safety in Case of Fire		
Reaction to fire	Class E	
Resistance to fire	ETA 17/0392 Annex A	
Hygiene, Health and Environment		
Air Permeability	ETA 17/0392 Annex B	
Water Permeability	NPD	
Dangerous Substances	Uses categories IA3, S/W3	
Safety in use		
Mechanical resistance and stability	NPD	
Resistance to impact/movement	NPD	
Adhesion	NPD	
Protection against noise		
Airborne sound insulation	ETA 17/0392 Annex C	
Energy, Economy and Heat Retention		
Thermal properties	NPD	
Water vapour permeability	NPD	
General aspects relating to fitness for use		
Service & Durability	Z_1	