

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**

- **Trade name:** Nullifire FC215

- **MSDS code:** W-N-FC215

- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

- **Application of the substance / the mixture** Thinner, Diluent

- **1.3 Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

tremco illbruck Coatings Ltd
Coupland Road, Hindley Green, WIGAN, WN2 4HT
Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410
msds@tremco-illbruck.com

- **Further information obtainable from:**

Nullifire
Torrington Avenue, Coventry, CV4 9TJ
T: +44 (0) 2476855000, F: +44 (0) 2476469547
www.nullifire.com, protect@nullifire.com

- **1.4 Emergency telephone number:**

During office hours tel.: +44 (0) 2476855000. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**

- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Contains:**

butanone
n-butyl acetate
Naphtha (petroleum), hydrodesulfurized heavy

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

Trade name: Nullifire FC215

(Contd. of page 1)

Naphtha (petroleum), hydrotreated light

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P235 Keep cool.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P331 Do NOT induce vomiting.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

- **Supplemental information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Solvent mixture

- **Dangerous components:**

CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	30- <50%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	30- <50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10- <20%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411	5- <10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

Trade name: Nullifire FC215

(Contd. of page 2)

CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix) Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5- <10%
CAS: 64742-82-1 EINECS: 265-185-4 Reg.nr.: 01-2119458049-33-xxxx	Naphtha (petroleum), hydrodesulfurized heavy Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	1- <5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Nausea

Irritating to eyes, respiratory system and skin.

May cause damage to organs through prolonged or repeated exposure.

Harmful: may cause lung damage if swallowed.

Repeated exposure may cause skin dryness or cracking.

· **Information for doctor:** No further relevant information available.

· **Hazards:** No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· **Protective equipment:**

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

(Contd. on page 4)

Trade name: Nullifire FC215

(Contd. of page 3)

· **Additional information**

- Cool endangered receptacles with water spray.
- Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

- Wear protective equipment. Keep unprotected persons away.
- Ensure adequate ventilation
- Keep away from ignition sources.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

- Ensure adequate ventilation.
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to item 13.
- Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

- Ensure good ventilation/exhaustion at the workplace.
- Avoid contact with the eyes and skin.
- Do not eat, drink, smoke or sniff while working.
- Do not breathe vapour.

· **Information about fire - and explosion protection:**

- Highly flammable liquid and vapour.
- Keep ignition sources away - Do not smoke.
- Fumes can combine with air to form an explosive mixture.
- Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

- Store only in unopened original receptacles.

· **Information about storage in one common storage facility:** Protect from heat and direct sunlight.

· **Further information about storage conditions:**

- Store in cool, dry conditions in well sealed receptacles.

· **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 5)

Trade name: Nullifire FC215

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

1330-20-7 xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

· Ingredients with biological limit values:

78-93-3 butanone

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

1330-20-7 xylene (mix)

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· Additional information:

The lists valid during the making were used as basis.
EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not breathe vapour.
Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.

· Respiratory protection:

Use only in well-ventilated areas.

(Contd. on page 6)

Trade name: Nullifire FC215

(Contd. of page 5)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

• **Material of gloves**

Rubber gloves

Plastic gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

• **Body protection:**

Protective work clothing

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

• **9.1 Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form: Liquid
Colour: Not determined.

• **Odour:** Solvent-like

• **Boiling point/Boiling range:** 80 °C

• **Flash point:** 1 °C

• **Ignition temperature:** 315 °C

• **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

• **Explosion limits:**

Lower: 1.2 Vol %
Upper: 11.5 Vol %

• **Vapour pressure at 20 °C:** 105 hPa

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

Trade name: Nullifire FC215

(Contd. of page 6)

- | | |
|--|--|
| · Density at 20 °C: | 0.87 g/cm ³ |
| · Solubility in / Miscibility with water: | Slightly soluble. |
| · Viscosity:
Dynamic at 20 °C: | 1 mPas |
| · Solvent content: | |
| Organic solvents: | 100.0 % |
| VOC (EU) | 870 g/l |
| VOC (EC) | 100 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** Stable
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong oxidising agents.
- **10.4 Conditions to avoid**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Nitrogen oxides
Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	4700 mg/kg (rat)
Inhalative	LC50/8 h	3670 ppmV (rat)

1330-20-7 xylene (mix)

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	3200 mg/kg (rabbit)
Inhalative	LC50/4 h	20 mg/L (rat)

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 3160 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.
- **Serious eye damage/irritation**
Causes serious eye irritation.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

Trade name: Nullifire FC215

(Contd. of page 7)

- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information· **12.1 Toxicity**· **Aquatic toxicity:****1330-20-7 xylene (mix)**

EC50/24 h	165 mg/L (daphnia magna)
LC50/96 h	21.0 mg/L (pimephales promelas)
	13.5 mg/L (Iepomis macrochirus)

64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

NOEC/21 d	0.097 mg/L (daphnia magna)
-----------	----------------------------

- **12.2 Persistence and degradability** Moderately / partly biodegradable
- **12.3 Bioaccumulative potential** Low potential for accumulating in organisms
- **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:****1330-20-7 xylene (mix)**

IC50/72 h	3-5 mg/L (selenstrum capricornutum)
-----------	-------------------------------------

- **Remark:**
The product is highly volatile.
Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
May cause long lasting harmful effects to aquatic life.
Do not allow product to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

Trade name: Nullifire FC215

(Contd. of page 8)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Waste disposal key:** UK (WM3) : HP3 HP4 HP5 HP6 HP14

- **European waste catalogue**

07 01 04*	other organic solvents, washing liquids and mother liquors
15 01 10*	packaging containing residues of or contaminated by dangerous substances

- **Uncleaned packaging:**

- **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN1263

- **14.2 UN proper shipping name**

- **ADR**

1263 PAINT RELATED MATERIAL

- **IMDG, IATA**

PAINT RELATED MATERIAL

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class**

3 (F1) Flammable liquids.

- **Label**

3

- **IMDG, IATA**



- **Class**

3 Flammable liquids.

- **Label**

3

- **14.4 Packing group**

- **ADR, IMDG, IATA**

II

- **14.5 Environmental hazards:**

- **Marine pollutant:**

No

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

Trade name: Nullifire FC215

(Contd. of page 9)

<ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: 	<p>Warning: Flammable liquids.</p> <p>33</p> <p>F-E, S-E</p>
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L</p> <p>Code: E2</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 500 ml</p>
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	<p>2</p> <p>D/E</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>1L</p> <p>Code: E2</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 500 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 1263 PAINT RELATED MATERIAL, , II</p>

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"CHIP" SI 2009 No.716.

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015
- **National regulations:**
- **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.11.2015

Version number 1

Revision: 05.11.2015

Trade name: Nullifire FC215

(Contd. of page 10)

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3